

Technical drawing of a bolt with dimensions and fit specifications.

Top View Dimensions:

- Overall length: "B"
- Head diameter: 0.56 [14.2]
- Head thickness: 0.06 REF.
- Head width: 0.40 [10.2]
- Head to shank length: "A"
- Shank diameter: 0.156 (3.96) DIA. HOLE
- Shank length: 0.34 [8.6]
- Shank to nut length: 0.40 [10.2]
- Nut thickness: 0.06 REF.
- Nut width: 0.40 [10.2]
- Nut to head length: 0.40 [10.2]

Fit Specifications:

- FITS 0.187 (4.75) TO 0.192 (4.88) DIA. HOLE
- PANEL THICKNESS 0.03 (0.76) TO 0.08 (2.03)

Bottom View Dimensions:

- Overall length: 0.22 [5.6]
- Head diameter: 0.13 DIA. [3.3]
- Head thickness: 0.06 REF.
- Head width: 0.40 [10.2]
- Head to shank length: 0.40 [10.2]
- Shank diameter: 0.156 (3.96) DIA. HOLE
- Shank length: 0.34 [8.6]
- Shank to nut length: 0.40 [10.2]
- Nut thickness: 0.06 REF.
- Nut width: 0.40 [10.2]
- Nut to head length: 0.40 [10.2]

PANDUIT PART NO. *	"A" in/mm	"B" in/mm	WEIGHT lbs/100 (g)/pcs
CBLS18	0.18 (4.6)	0.92 (23.4)	0.024 (11)
CBLS25	0.25 (6.4)	0.98 (24.9)	0.051 (23)
CBLS37	0.37 (9.4)	1.11 (28.2)	0.075 (34)
CBLS50	0.50 (12.7)	1.23 (31.2)	0.099 (45)
CBLS62	0.62 (15.7)	1.35 (34.3)	0.123 (56)
CBLS75	0.75 (19.1)	1.48 (37.6)	0.150 (68)

* SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX, DESIGNATION FOR PACKAGE SIZE AND PART COLOR.

CAD FILENAME/LAYERS	DESCRIPTION
01	01
02	02
03	03
04	04
05	05
06	06
07	07
08	08
09	09
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

PANDUIT

CORP. TINLEY PARK, ILLINOIS

CBLS

CIRCUIT BOARD LOCKING SUPPORT

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ± 0.1 (2.5) (.XXX) ± 0.020 (.5)
(.XX) ± 0.05 (1.3) ANGLES $\pm 5^\circ$

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY	LGG
----------	-----

MAT'L:

	SCALE
--	-------

2X

DATE	6/13/01
------	---------

NYLON 6/6

DRAWING NO.

GB0239HL

DWG
A
SIZE

R	6-13-01	LGG		CHANGED DRAWING FROM SS-18657 (RV 4)	GB0239HL	R				
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP		